

STYLING















DRIVING



INTERIOR



POWERTRAIN

GREEN DIESEL ENGINE EURO III

DISPLACEMENT	3.0L	
RATED OUTPUT (kW(HP)/rpm)	110 (148)/3400	
MAX TORQUE (N.m/rpm)	370/2000	
COMPRESSION RATIO	17.3:1	



HIGH CAPACITY TURBO CHARGER

To achieve the maximum power & torque by lower engine capacity and hence improve fuel efficiency

JAPANESE TECHNOLOGY

Exhaust Gas Recirculation (EGR)



SAFETY














Anti Lock Braking System

ABS Can protect the wheel being locked or slipped to ensure the valid braking under different ground conditions.



Electronic Brakeforce Distribution

EBD can detect automatically, the load of front and back wheels, rotation differences, or wheel locking by electronic means, and distribute ideal brake forces at proper time.



Monocoque Type Vehicle Body

- High-strength swaybars
- **Buffer Beams**



Specification





pecification	Standard Spec	Full Spec
ENGINE		
Engine	С	K5
	In Line 4 Cylinder Common Rail Turbocharged With Intercooler, EGR, Diesel Eng	
Bore x Stroke	96 x 103	
Emission Standard	Euro III	
Displacement (L)	2.982L	
Rated Output (kW(HP)/RPM)	110(148)/3400	
Max. Torque (N.M/R.P.M)	370/2000	
Compression Ratio	17.3:1	
Top Speed *	135 km/h	
Fuel Standard	Euro-III Diesel or Above	
Fuel Tank Capacity (L)	70	Litre
DRIVING SYSTEM		
Transmission Type	Manual 5-Speed	
Gear Ratio	1st: 4.313, 2nd: 2.330, 3rd: 1.436, 4th: 1.000, 5th:0.838, Peverse: 4.22	
Clutch	Single Disc, Hydraulic Control	
Driving Type	Front Engine, Rear Drive	
Brake System	ABS+EBD, Intelligent Brake Assisance System	
•	Front Disc & Rear Drum	
Suspension	Front Transverse Double Wishbone Independent Suspension,	
	Rear Variable Rate Leaf Spring	
	near variable nate	Lear Spring
TECHNICAL DIMENSION		
Overall LxWxH (mm)	5470 x 1885	v 2285
Wheelbase (mm)	3110	X 2203
Ground Clearance (mm)	169	
Gross Vehicle Weight (kg)	3500	
Curb Weight (kg)*	2415	
Seating Capacity Tire	15 Seats 205R/15C	
	12.2	
Minimum Turning Radius (m)	12.2	
FEATURES AND ACCESSORIES		
Audio Systems	Display Audio With 7" Touch Screen L	1
Stereo Speaker	2 pcs	6 pcs
Reverse Camera	•	•
Reverse Sensor	•	•
Cabin Light	•	•
Seat Material	Black PU & Lint	
Last Row Hanging Seat	•	•
Intermittent Front Wiper, Rear Wiper	•	•
Rear Windscreen with Demister	•	•
Tiltable Steering Wheel	•	•
Central Locking	•	•
Remote Control	-	•
Side Mirror with LED Turning Signal Lamp	•	•
Side Mirror Adjustment	Po	wer
High-Mounted 3rd Brake Lamp	•	•
Projection Headlamp with DRL	•	•
Front Fog Lamp	•	•
Wheel Size	15" Steel	15" Alloy
Air-Conditioner - Front	•	•
Air-Conditioner - Rear	9 Air Vents	6 Air Vents
Rear Evaporator	Single	Double
Middle Console Box with 3 Cup Holder	-	• Double
Luxury PVC Roof Lining	•	•
PVC Floor Mat	•	•
Power Window - Driver & Co-driver	•	•
1 OWCI WINDOW - DIIVEI & CO-UNVEI	-	-

^{*}Data collected under testing conditions. The final results may differ due to different driving conditions, overall vehicle weight etc.















WHY CHOOSE KINGO VAN?

FACTORY BUS/SCHOOL BUS





22 **MURID-MURID**

AMBULANCE





TALL & WIDE **INTERIOR**

SEMI PANEL VAN





CARRY 5 PEOPLE

HEARSE VAN





MUSLIM **HEARSE** VAN

MOBILE OFFICE





VERSATILE SET UP

VIP LIMOUSINE





LUXURY INTERIOR

EXECUTIVE TRANSPORTER





COMFORTABLE RIDE & AMPLE **LUGGAGE SPACE**




AUTOMATED WHEELCHAIR LIFT


DIMENSION







SEATING LAYOUT



15 Seats (2+3+3+3+4)







Branch & Dealer Chop



R&A MARKETING SDN BHD

CONSISTENT | ACTIVE | MOBILE Sole Distributor of King Long Minivan

Sendok Group Building, Lot 1564, Batu 4, 42100 Klang, Selangor Darul Ehsan, Malaysia. Email: info@sendokgroup.com Tel: +603-3345 5600 Fax:+03-3291 9658





Disclaimer: All features & specification shown in this brochure is subject to change without prior notice and may vary according to locality. The color(s) of the vehicle(s) and interior shown here in may slightly differ from actual vehicle.



Anti-Glare Rear View Mirror













